

**NASA TECHNICAL
MEMORANDUM**

NASA TM X-64605

**A FIRST-ORDER THEORY FOR ROTATING
GRAVITY GRADIOMETERS**

By Robert L. Holland
Space Sciences Laboratory

April 16, 1971

**CASE FILE
COPY**

COPY

NASA

*George C. Marshall Space Flight Center
Marshall Space Flight Center, Alabama*

1. REPORT NO. NASA TM X-64605	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO.	
4. TITLE AND SUBTITLE A First-Order Theory for Rotating Gravity Gradiometers		5. REPORT DATE April 16, 1971	
		6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S) Robert L. Holland		8. PERFORMING ORGANIZATION REPORT #	
9. PERFORMING ORGANIZATION NAME AND ADDRESS George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812		10. WORK UNIT NO.	
		11. CONTRACT OR GRANT NO.	
12. SPONSORING AGENCY NAME AND ADDRESS National Aeronautics and Space Administration Washington, D. C. 20546		13. TYPE OF REPORT & PERIOD COVERED Technical Memorandum	
		14. SPONSORING AGENCY CODE	
15. SUPPLEMENTARY NOTES Prepared by Space Sciences Laboratory, Science and Engineering			
16. ABSTRACT The equations of motion for a rotating gradiometer are developed and specialized to a forced harmonic oscillator model that may be solved analytically. Numerical results are given comparing the analytical approximation to numerical integration of the exact equations.			
17. KEY WORDS Gravity gradient Gravimeters Torque Forced harmonic Contracted alternating oscillator product Gradiometers Mass detector Gravitational field		18. DISTRIBUTION STATEMENT Unclassified - unlimited <i>Robert L. Holland</i>	
19. SECURITY CLASSIF. (of this report) Unclassified	20. SECURITY CLASSIF. (of this page) Unclassified	21. NO. OF PAGES 25	22. PRICE \$3.00

A FIRST-ORDER THEORY FOR ROTATING GRAVITY GRADIOMETERS

SUMMARY

The equations of motion for a rotating gradiometer are developed and specialized to a forced harmonic oscillator model that may be solved analytically. Numerical results are given comparing the analytical approximation to numerical integration of the exact equations.

INTRODUCTION

A rotating gradiometer may be visualized as two perpendicular dumbbells coupled at their centers by a mechanical torsional spring pivot. Gradiometers have been studied experimentally and theoretically for application to a variety of problems involving the measurement of gravitational fields [1-3].

Since the gravitational torque on each dumbbell of the rotating gradiometer is opposite (and equal if they have equal moments of inertia), there will be a deflection of the spring pivot coupling. This deflection is the quantity that is observed and related to the torque which may then be related to the external gravitational field and mass.

The general relationship for the torque on any rigid body because of an external gravitational field is presented in the Appendix. This report begins with that basic relationship and develops the specific equations for a rotating gradiometer. Conditions at resonance are also discussed since the gradiometer may be rotated at a speed commensurate with the fundamental frequency of the spring to give a resonant condition.

GENERAL EQUATIONS

As shown in the Appendix, the gravitational torque on any rigid body is given by

$$\vec{N} = -G \int_m V, (\bigcirc) I \, d m \quad , \quad (1)$$

where G is the universal gravitational constant, m is the external mass, I is the moment of inertia matrix of the rigid body, and $V,$ is the gravity-gradient matrix of the gravitational field generated by m . It is also shown in the Appendix that equation (1) is invariant under orthonormal coordinate transformations.

If m is considered a spherical homogeneous mass and \vec{N} , V , and I are referred to the principal axes of the small body, equation (1) becomes

$$\vec{N}' = \frac{3mG}{R^5} \vec{R}' \times I' \vec{R}' \quad , \quad (2)$$

where the primes indicate that the quantities are referred to the principal axes of the small body and I' is the diagonalized moment of inertia matrix of the small body; i.e.,

$$I' = \begin{bmatrix} A & 0 & 0 \\ 0 & B & 0 \\ 0 & 0 & C \end{bmatrix} \quad .$$

Figure 1 gives the geometrical relationship of the prime system (fixed along the principal axes of dumbell no. 1), the unprimed system (fixed in the laboratory), and the \vec{R} vector.

The torque on dumbell no. 1 referred to the x, y, z system may be written as

$$\vec{N} = \frac{3mG}{R^3} \vec{R} \times T I' T^T \vec{R} \quad , \quad (3)$$




Figure 1. Geometry of principal coordinates and laboratory coordinates.

where T is the transformation matrix from the primed (principal) axes of dumbbell no. 1; i.e.,

$$T = \begin{bmatrix} \cos \theta_1 & -\sin \theta_1 & 0 \\ \sin \theta_1 & \cos \theta_1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

and

$$\vec{R} = \begin{bmatrix} R \cos \theta \cos \phi \\ R \cos \theta \sin \phi \\ R \sin \theta \end{bmatrix} \equiv \begin{bmatrix} R_x \\ R_y \\ R_z \end{bmatrix}$$

After denoting the principal moments of inertia of dumbell no. 1 as A_1 , B_1 , and C_1 , it is assumed that $A_1 \cong 0$ and $B_1 = C_1$. Thus, I_1' becomes

$$I_1' = \begin{bmatrix} 0 & 0 & 0 \\ 0 & C_1 & 0 \\ 0 & 0 & C_1 \end{bmatrix} .$$

Using these results in equation (3) gives

$$\vec{N}_1 = \begin{bmatrix} N_x^{(1)} \\ N_y^{(1)} \\ N_z^{(1)} \end{bmatrix} = \begin{bmatrix} \frac{3mGC_1}{R^5} (R_y R_z \sin^2 \theta_1 + R_x R_z \sin \theta_1 \cos \theta_1) \\ \frac{3mGC_1}{R^5} (-R_x R_z \cos^2 \theta_1 + R_y R_z \sin \theta_1 \cos \theta_1) \\ \frac{3mGC_1}{R^5} \left[(R_y^2 - R_x^2) \frac{1}{2} \sin 2 \theta_1 + R_x R_y \cos 2 \theta_1 \right] \end{bmatrix} . \quad (4)$$

Similarly, the gravity-gradient torque on dumbell no. 2 is

$$\vec{N}_2 = \begin{bmatrix} N_x^{(2)} \\ N_y^{(2)} \\ N_z^{(2)} \end{bmatrix} = \begin{bmatrix} \frac{3mGC_2}{R^5} (R_y R_z \sin^2 \theta_2 + R_x R_z \sin \theta_2 \cos \theta_2) \\ \frac{3mGC_2}{R^5} (-R_x R_z \cos^2 \theta_2 + R_y R_z \sin \theta_2 \cos \theta_2) \\ \frac{3mGC_2}{R^5} \left[(R_y^2 - R_x^2) \frac{1}{2} \sin 2 \theta_2 + R_x R_y \cos 2 \theta_2 \right] \end{bmatrix} . \quad (5)$$

Now assuming that the deflection of one of the dumbells with respect to the other is restricted to the x, y plane that coincides with the x', y' plane, then only the N_z components of the torque contribute to this deflection. This allows equating the third component of the torque to the rate of change of angular momentum along the z axis. Before doing this, however, the restoring and damping torques will be formulated.

The restoring torque on dumbell no. 2 is

$$N_2^{(R)} = -k\alpha \quad , \quad (6)$$

and the damping torque on dumbell no. 2 is

$$N_2^{(D)} = -h\dot{\alpha} \quad , \quad (7)$$

where k and h are assumed constant. Likewise, the restoring torque on dumbell no. 1 is

$$N_1^{(R)} = k\alpha \quad , \quad (8)$$

and the damping torque on dumbell no. 1 is

$$N_1^{(D)} = h\dot{\alpha} \quad . \quad (9)$$

The sum of all the torques on dumbell no. 1 may be equated to $C_1\ddot{\theta}_1$, and a similar operation may be performed for dumbell no. 2. Thus,

$$C_1\ddot{\theta}_1 = h\dot{\alpha} + k\alpha + \frac{3mGC_1}{R^5} \left[(R_y^2 - R_x^2) \frac{1}{2} \sin 2\theta_1 + R_x R_y \cos 2\theta_1 \right] \quad (10)$$

and

$$C_2\ddot{\theta}_2 = -h\dot{\alpha} - k\alpha + \frac{3mGC_2}{R^5} \left[(R_y^2 - R_x^2) \frac{1}{2} \sin 2\theta_2 + R_x R_y \cos 2\theta_2 \right] \quad . \quad (11)$$

It is observed from Figure 1 that

$$\theta_2 - \theta_1 = \frac{\pi}{2} + \alpha \quad , \quad (12)$$

then

$$\ddot{\theta}_2 - \ddot{\theta}_1 = \ddot{\alpha} \quad .$$

Using these results in equations (10) and (11), a differential equation for α and θ_1 may be written as

$$\ddot{\alpha} = - \left(\frac{h}{C_2} + \frac{h}{C_1} \right) \dot{\alpha} - \left(\frac{k}{C_1} + \frac{k}{C_2} \right) \alpha + \frac{3mG}{2R^5} (R_y^2 - R_x^2) (\sin 2\theta_2 - \sin 2\theta_1) + \frac{3mG}{R^5} R_x R_y (\cos 2\theta_2 - \cos 2\theta_1) \quad (13)$$

and

$$\ddot{\theta}_1 = \frac{h}{C_1} \dot{\alpha} + \frac{k}{C_1} \alpha + \frac{3mG}{R^5} \left[(R_y^2 - R_x^2) \frac{1}{2} \sin 2\theta_1 + R_x R_y \cos 2\theta_1 \right] \quad (14)$$

Replacing θ_2 with $\theta_1 + \alpha + \frac{\pi}{2}$ from equation (12) gives the following differential equations for $\ddot{\alpha}$ and $\ddot{\theta}_1$ as functions of α and θ_1 :

$$\begin{aligned} \ddot{\alpha} = & -H \dot{\alpha} - K \alpha + \frac{3mG}{2R^5} (R_y^2 - R_x^2) (-\sin 2\theta_1 \cos 2\alpha - \cos 2\theta_1 \sin 2\alpha \\ & - \sin 2\theta_1) + \frac{3mG}{R^5} R_x R_y (-\cos 2\theta_1 \cos 2\alpha \\ & + \sin 2\theta_1 \sin 2\alpha \\ & - \cos 2\theta_1) \quad (15) \end{aligned}$$

and

$$\ddot{\theta}_1 = \frac{h}{C_1} \dot{\alpha} + \frac{k}{C_1} \alpha + \frac{3mG}{R^5} \left[(R_y^2 - R_x^2) \frac{1}{2} \sin 2\theta_1 + R_x R_y \cos 2\theta_1 \right] \quad (16)$$

where

$$H = \frac{h}{C_1} + \frac{h}{C_2} \quad \text{and} \quad K = \frac{k}{C_1} + \frac{k}{C_2}$$

These are the exact differential equations for a spherical homogeneous perturbing mass generating a torque on the coupled dumbbells where the

restoring torque is proportional to the deflection (α) of the spring coupling and the damping torque is proportional to the angular velocity ($\dot{\alpha}$) of the spring coupling.

FORCED HARMONIC OSCILLATOR EQUATIONS

Equations (15) and (16) are not forced harmonic equations for the deflection, and certain assumptions are necessary before they can be reduced to forced harmonic equations. First, the small angle approximation must be made for α so that $\cos 2\alpha \cong 1$ and $\sin 2\alpha \cong 2\alpha \cong 0$. The second assumption that is necessary is to assume that R_x , R_y , and R_z are constant. A third assumption is that $\theta_1 = \omega t$ where $\omega = \text{constant angular rate}$.

If the above assumptions are made, then

$$\ddot{\alpha} + H\dot{\alpha} + K\alpha = -\frac{3mG}{R^3}(R_y^2 - R_x^2) \sin 2\omega t - \frac{6mG}{R^3} R_x R_y \cos 2\omega t \quad (17)$$

and

$$\theta_1 = \omega t \quad (18)$$

Since $\vec{R} = (R_x, R_y, R_z)$ is assumed constant, it may be assumed that \vec{R} lies along the x axis without any loss of generality since this is equivalent to assuming that the x axis is along \vec{R} initially; then,

$$\ddot{\alpha} + H\dot{\alpha} + K\alpha = \frac{3mG}{R^3} \sin 2\omega t, \quad (19)$$

which is the forced harmonic oscillator equation.

SOLUTION OF THE FORCED HARMONIC OSCILLATOR EQUATION

The solution to equations of the form of equation (19) are well known. An excellent discussion of the solutions may be found in Reference 5.

The solution to equation (19) for $\frac{H}{2} < K$ may be written as

$$\alpha = e^{-bt} (A_1 \cos qt + A_2 \sin qt) + \frac{a}{p} \sin(2\omega t - \beta) \quad , \quad (20)$$

where

$$b = \frac{H}{2} \quad , \quad q = \sqrt{n^2 - b^2} \quad , \quad n^2 = K \quad ,$$

$$a = \frac{3mG}{R^3} \quad , \quad p = \sqrt{[n^2 - (2\omega)^2]^2 + (4b\omega)^2} \quad ,$$

$$\tan \beta = \frac{4b\omega}{n^2 - (2\omega)^2} \quad ,$$

and A_1 and A_2 are initial integration constants.

One quantity that is usually of interest is the time constant τ , which is sometimes referred to as the relaxation time or the $\frac{1}{e}$ folding time. This is the time required for the first term (transient term) to reach $\frac{1}{e}$ of its original value. This occurs when $b\tau = 1$; i.e., $\tau = \frac{1}{b} = \frac{2}{H}$ which is seen to depend on the damping of the oscillator. When $t \rightarrow \infty$, the transient term goes to zero. This is the transient time that is seen to take several time constants to get down to one-hundredth or one-thousandth of the initial value. After the transient time, the oscillator is considered to be in steady state with amplitude

$$\frac{a}{p} = \frac{\frac{3mG}{R^3}}{\{[n^2 - (2\omega)^2]^2 + (4b\omega)^2\}^{1/2}} \quad . \quad (21)$$

or for $n \gg \frac{1}{\tau} = b$,

$$Q = \frac{n}{2b} = \frac{n\tau}{2} ; \quad (26)$$

and from equation (24) ,

$$f = \frac{1}{2n\tau} , \quad (27)$$

which gives

$$2f = \frac{1}{2Q} . \quad (28)$$

This indicates that a high f and high Q are incompatible.

COMPARISONS AND RESULTS

The results of the forced harmonic solution and numerical integration of equations (15) and (16) are shown in Table 1. The initial conditions assumed were as follows:

$$K = (4\pi)^2 \text{ radians/sec}^2 ,$$

$$H = 0.404 \text{ radian/sec} ,$$

and

$$\omega = 2\pi \text{ radians/sec} .$$

As can be seen, the steady-state results agree through the third significant figure. From these results, it may be concluded that the forced harmonic oscillator approximation is sufficient for design purposes. It should be noted that the forced harmonic oscillator theory assumes a linear spring constant and damping coefficient.

Another point of interest is the driving frequency ω required to give maximum steady-state amplitude. This occurs when p is a minimum; thus, differentiating p with respect to 2ω and equating the result to zero gives the conditions

$$(2\omega)^2 = n^2 - 2b^2$$

or

$$p = 2b\sqrt{n^2 - b^2} \quad (22)$$

for maximum amplitude. These results may be used for determining the best operating conditions of a gradiometer.

Savet [3] has suggested a figure of merit f for various sensors defined as the sensitivity σ divided by the time constant squared τ^2 . The sensitivity is defined as the steady-state displacement amplitude divided by the amplitude of the forcing term. This figure of merit in the present discussion turns out to be

$$f \equiv \frac{\sigma}{\tau^2} = \left(\frac{a}{p} \div a \right) \div \tau^2 = \frac{1}{p} \div \tau^2 = \frac{1}{p\tau^2} \quad (23)$$

Using equation (22) in the above,

$$f = \frac{1}{2b\tau^2\sqrt{n^2 - b^2}} = \frac{1}{2\tau\sqrt{n^2 - \frac{1}{\tau^2}}} \quad (24)$$

If the quality amplification factor, Q is defined as the energy stored in the spring divided by the energy dissipated per cycle at resonance and steady state, then

$$Q = \frac{2\pi}{1 - e^{-4\pi/\tau\sqrt{n^2 - \frac{1}{\tau^2}}}} = \frac{2\pi}{1 - e^{-8\pi f}} \quad (25)$$

TABLE 1. POINTS IN STEADY STATE FOR 1 c/s

Numerical Integration		Forced Harmonic Oscillation Solution	
Time (sec)	Delta (radians $\times 10^{-9}$)	Time (sec)	Delta (radians $\times 10^{-9}$)
30.0125	-0.59040669	30.0000	-0.59015672
30.2625	0.59056961	30.2500	0.59034407
32.0125	-0.59143408	32.0000	-0.59142200
32.2625	0.59152283	32.2500	0.59154729
33.0125	-0.59174430	33.0000	-0.59188750
33.2625	0.59180415	33.2500	0.59198996
42.025	-0.59316773	42.0000	-0.59363485
42.275	0.59323604	42.2500	0.5936516
Steady State			
29.5125	-0.59004683	30.0000	-0.59015672

Figure 2 shows the waveform for 20 sec, which indicates that the transient term lasts for about 4τ since τ is 5 sec for this case.




Figure 2. Waveform for 20 sec for 1 c/s run.

APPENDIX

THE GRAVITY-GRADIENT TORQUE AS A CONTRACTED ALTERNATING PRODUCT

THE GRAVITATIONAL TORQUE OF ONE RIGID BODY ON ANOTHER

To establish explicit invariant relationships between the moment of inertia of a small body, the gravity gradient because of the presence of larger bodies, and the torque on the small body, it is necessary to define the moment of inertia and gravity gradient in such a way that their transformation properties are known.

The Moment of Inertia

From Figure 1-A, the moment of inertias usually are defined as

$$I_{ij} = \begin{cases} - \int_m \rho_i \rho_j dm & \text{for } i \neq j \\ \int_m (\rho^2 - \rho_i^2) dm & \text{for } i = j \end{cases}, \quad (A-1)$$

where $\vec{\rho} \equiv (\rho_1, \rho_2, \rho_3)$, $i \equiv \{1, 2, 3\}$, and $j \equiv \{1, 2, 3\}$. To check the transformation properties of I_{ij} , an orthonormal Cartesian coordinate transformation M is defined such that $\vec{\rho} = M\vec{\rho}'$; i.e.,

$$\rho_i = M_{ip'} \rho_{p'}$$

and

$$\rho_j = M_{jq'} \rho_{q'}$$

Then, equation (A-1) becomes for $i \neq j$




FIGURE 1-A. Geometry of Inertial Coordinates Fixed at the Center of Mass of Large and Small Rigid Bodies

$$\begin{aligned}
I_{ij} &= - \int_m M_{ip'} \rho_{p'} M_{jq'} \rho_{q'} dm = - \int_m M_{ip'} \rho_{p'} \rho_{q'} M_{iq'} dm \\
&= - M_{ip'} \left(\int_m \rho_{p'} \rho_{q'} dm \right) M_{jq'} = M_{ip'} I_{p'q'} M_{jq'} \\
&= (MI')_{iq'} M_{jq'} = (MI' M^T)_{ij} \quad . \quad (A-2)
\end{aligned}$$

Thus, $I = MI' M^T$ for $i \neq j$. For $i = j$, the integrals in equation (A-1) are all of the form $\int_m \rho_i \rho_i dm$, which will also transform according to equation (A-2).

The Gravity Gradient

The gravity gradient is usually defined as the second partial derivatives of a potential function, say $V(x_1, x_2, x_3)$. Then,

$$V_{,ij} \equiv \frac{\partial^2 V}{\partial x_j \partial x_i} \quad . \quad (A-3)$$

To check the transformation properties of $V_{,ij}$ an orthonormal Cartesian coordinate transformation M is defined such that $\vec{x} = M\vec{x'}$. Thus,

$$x_i = M_{ip'} x_{p'} \quad , \quad x_{p'} = M_{p'i} x_i \quad ,$$

$$x_j = M_{jq'} x_{q'} \quad , \quad \text{and} \quad x_{q'} = M_{q'j} x_j \quad .$$

Now,

$$\begin{aligned}
 V_{,ij} &= \frac{\partial}{\partial x_j} \left(\frac{\partial V}{\partial x_i} \right) = \frac{\partial}{\partial x_j} \left(\frac{\partial V}{\partial x_{p'}} \frac{\partial x_{p'}}{\partial x_i} \right) = \frac{\partial}{\partial x_j} \frac{\partial V}{\partial x_{p'}} M_{p'i} \\
 &= \frac{\partial}{\partial x_{q'}} \frac{\partial V}{\partial x_{p'}} \frac{\partial x_{q'}}{\partial x_j} M_{p'i} = \frac{\partial^2 V}{\partial x_{q'} \partial x_{p'}} M_{q'j} M_{p'i} \\
 &= V_{,p'q'} M_{q'j} M_{p'i} = M_{p'i} V_{,p'q'} M_{q'j} \\
 &= M_{p'i} (V, M^T)_{p'j} = \left[(M^T)^T V, M^T \right]_{ij} = (MV, M^T)_{ij} .
 \end{aligned}$$

Thus, $V_{,} = MV, M^T$. (A-4)

The Torque as the CAP Product of $V_{,}$ and I

From Figure 1, the element of force $d(\vec{dF})$ on the element of mass dm because of the element of mass dm^* is

$$d(\vec{dF}) = -Gdm dm^* \frac{\vec{d}}{d^3} \equiv -Gdm dm^* \vec{f}(\vec{d}) . \quad (A-5)$$

However, since $\vec{d} = \vec{r} + \vec{\rho}$ and it is assumed that $\rho \ll r$, then the i^{th} component of $\vec{f}(\vec{d})$ is [4]

$$f_i(\vec{d}) = f_i(\vec{r} + \vec{\rho}) \doteq f_i(\vec{r}) + \frac{\partial f_i}{\partial x_j} \rho_j \equiv f_i(\vec{r}) + V_{,ij} \rho_j . \quad (A-6)$$

Where

$$\vec{r} \equiv (x_1, x_2, x_3), \quad \vec{\rho} \equiv (\rho_1, \rho_2, \rho_3) ,$$

$$f_i \equiv \frac{\partial V}{\partial x_i} , \quad \text{and} \quad V \equiv \frac{1}{d} .$$

Now, substituting equation (A-6) into equation (A-5),

$$d(d\vec{F}) = -Gdm dm * [\vec{f}(\vec{r}) + V, \vec{\rho}]$$

The torque about 0 because of the force of dm^* on dm is

$$\begin{aligned} d(d\vec{N}) &= \vec{\rho} \times d(d\vec{F}) = -Gdm dm * \vec{\rho} \times [\vec{f}(\vec{r}) + V, \vec{\rho}] \\ &= -Gdm dm * \vec{\rho} \times \vec{f}(\vec{r}) - Gdm dm * \vec{\rho} \times V, \vec{\rho} \end{aligned}$$

Integrating first over m gives

$$d\vec{N} = -Gdm * \int_m \vec{\rho} \times \vec{f}(\vec{r}) dm - Gdm * \int_m \vec{\rho} \times V, \vec{\rho} dm \quad (A-7)$$

The first integral on the right is zero because of the choice of 0 as the center of mass for m . The cross product in equation (A-7) is

$$\vec{\rho} \times V, \vec{\rho} = \begin{bmatrix} \rho_2 V, 3j \rho_j - \rho_3 V, 2j \rho_j \\ \rho_3 V, 1j \rho_j - \rho_1 V, 3j \rho_j \\ \rho_1 V, 2j \rho_j - \rho_2 V, 1j \rho_j \end{bmatrix}$$

Expanding and integrating over M gives

$$d\vec{N} = -Gdm * \begin{bmatrix} V, 2j I_{3j} - V, 3j I_{2j} \\ V, 3j I_{1j} - V, 1j I_{3j} \\ V, 1j I_{2j} - V, 2j I_{1j} \end{bmatrix}$$

$$= -Gdm* \begin{bmatrix} (V,I)_{23} - (V,I)_{32} \\ (V,I)_{31} - (V,I)_{13} \\ (V,I)_{12} - (V,I)_{21} \end{bmatrix} \quad (A-8)$$

As a notation convenience, it may be observed that the result in equation (A-8) may be obtained by placing the column or row vectors of V , and I in a determinant and using the conventional cross product rule except that the dot product is used when multiplying the column vectors. Using the Contracted Alternating Product (CAP) symbol \bigcirc to indicate this operation between V , and I , one has

$$V, \bigcirc I = \begin{bmatrix} e_1 & e_2 & e_3 \\ \vec{V}_1 & \vec{V}_2 & \vec{V}_3 \\ \vec{I}_1 & \vec{I}_2 & \vec{I}_3 \end{bmatrix} = \begin{bmatrix} \vec{V}_2 \cdot \vec{I}_3 - \vec{V}_3 \cdot \vec{I}_2 \\ \vec{V}_3 \cdot \vec{I}_1 - \vec{V}_1 \cdot \vec{I}_3 \\ \vec{V}_1 \cdot \vec{I}_2 - \vec{V}_2 \cdot \vec{I}_1 \end{bmatrix}, \quad (A-9)$$

which is the same as equation (A-8) since $\vec{V}_i \equiv (V_{i1}, V_{i2}, V_{i3})$, $\vec{I}_i \equiv (I_{i1}, I_{i2}, I_{i3})$ and both V , and I are symmetric. Thus, the torque given in equation (A-8) may be written as the CAP product of V , and I as

$$d\vec{N} = -Gdm* V, \bigcirc I$$

or

$$\vec{N} = -G \int_{m*} V, \bigcirc Idm* \quad (A-10)$$

This is considered to be desirable since it has the effect of separating or isolating those effects that depend on the field which is in V , and those that depend on the physical characteristics of the body which is in I . It also gives their relationship to the torque.

The Torque Referred to a Coordinate System in Which I is Diagonal

It may be shown that applying an orthonormal transformation to the CAP product of two matrices (or tensors) is the same as the CAP product of the transformed matrices (or tensors). It has already been seen that V , and I transform according to equations (A-2) and A-4; then, if M is the transformation from \bar{N}' to N ,

$$\begin{aligned}\vec{dN} &= M\vec{dN}' = -Gdm^* MV; (\bigcirc) I = -Gdm^* MV; M^T (\bigcirc) MI'M^T \\ &= -Gdm^* V, (\bigcirc) I\end{aligned}$$

or

$$\vec{N} = -G \int_{m^*} V, (\bigcirc) Idm^* \quad (A-11)$$

From the preceding discussion it is clear that to refer the torque \vec{N} to a particular coordinate system, both V , and I must also be referred to that system. For example, I may be diagonalized by referring I to the principal axes of M . In this system, the CAP product becomes

$$V', (\bigcirc) I' = \begin{bmatrix} V'_{,23}(I'_{22} - I'_{33}) \\ V'_{,23}(I'_{33} - I'_{11}) \\ V'_{,12}(I_{11} - I'_{22}) \end{bmatrix}, \quad (A-12)$$

where the primes indicate that the quantities are referred to the principal axes of m . From equation (A-12), the torque in the primed system depends on the three cross gradients; however, if the torque is transformed by a general rotation of coordinate axes, each component of the torque depends on all five of the independent gradient elements as indicated by equation (A-9).

The Torque of a Spherically Symmetric Homogeneous Body on a Small Distant Body

If m^* is spherically symmetric, then $\vec{\rho}^* = (0, 0, 0)$ in Figure 1-A so that $\vec{r} = \vec{R} - \vec{\rho}^* = \vec{R}$; then,

$$\vec{f}(\vec{r}) = f(\vec{R} - \vec{\rho}^*) = f(\vec{R}) = \frac{\vec{R}}{R^3}$$

$$V'_{,23} = \frac{\partial f_2}{\partial R_3} = - \frac{3R_3 R_2}{R^5}$$

$$V'_{,13} = \frac{\partial f_1}{\partial R_3} = - \frac{3R_3 R_1}{R^5}$$

$$V'_{,12} = \frac{\partial f_1}{\partial R_2} = - \frac{3R_1 R_2}{R^5}$$

Substituting the above into equation (A-10) and integrating gives

$$\vec{N} = \frac{3MG}{R^5} \vec{R}' \times I' \vec{R}' \quad , \quad (A-13)$$

where

$$\vec{R} \equiv (R_1, R_2, R_3) \quad .$$

This is the same result as used in Reference 6.

SUMMARY

An explicit relationship has been developed between the gravity gradient, moment of inertia, and torque of one large rigid body on another small body. From this theory, conclusions can be drawn concerning observable quantities and derived information from the observables. Also various applications, measurement concepts, and analysis techniques can be developed.

REFERENCES

1. Trageser, Milton B.: A Gradiometer System for Gravity Anomaly Surveying. Advances in Dynamic Gravimetry, Proceedings of the Symposium on Dynamic Gravimetry, March 16-17, 1970, Fort Worth, Texas, Published by the Instrument Society of America.
2. Bell, Curtis C.; Forward, Robert L.; and Williams, Harvel P.: Simulated Terrain Mapping with the Rotating Gravity Gradiometer. Advances in Dynamic Gravimetry, Proceedings of the Symposium on Dynamic Gravimetry, March 16-17, 1970, Fort Worth, Texas, Published by the Instrument Society of America.
3. Savet, Paul H.: Gravity Field Exploration by a New Gradient Technique. J. Spacecraft and Rockets, vol. 6, no. 6, June 1969.
4. Roberson, Robert E.; and Tatistcheff, D.: The Potential Energy of a Small Rigid Body in the Gravitational Field of an Oblate Spheroid. Journal of the Franklin Institute, vol. 262, 1956, pp. 209-214.
5. Brand, Louis: Differential and Difference Equations. John Wiley and Sons, Inc., New York, 1966.
6. Holland, Robert L.; and Sperling, Hans J.: A First-order Theory for the Rotational Motion of a Triaxial Rigid Body Orbiting an Oblate Primary. The Astronomical Journal, vol. 74, no. 3, April 1969.

APPROVAL

A FIRST-ORDER THEORY FOR ROTATING GRAVITY GRADIOMETERS

By Robert L. Holland

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

This document has also been reviewed and approved for technical accuracy.



ROBERT J. NAUMANN
Chief, Physics and Astrophysics Division



GERHARD B. HELLER
Director, Space Sciences Laboratory

DISTRIBUTION

INTERNAL

DIR

Dr. Rees

DEP-T

AD-S

Dr. Stuhlinger

S&E-DIR

Dr. Weidner

S&E-CSE-DIR

Dr. Haussermann

S&E-ASTR

Dr. Nurre

Mr. Hosenthien

Dr. Doanne

S&E-PD

Mr. Dudley

Mr. Kermit Hudson

S&E-R-DIR

Dr. Johnson

S&E-SSL-DIR

Mr. Gerhard Heller

Mr. Ray Hembree

S&E-SSL-C

Reserve (15)

S&E-SSL-S

Mr. Williams

Dr. Sieber

Mr. Loughhead

S&E-SSL-P

Dr. Naumann

S&E-SSL-PM

Mr. Robert Holland

Mr. Darbro

Mr. Parker

S&E-COMP-DIR

Dr. Hoelzer

S&E-COMP-DS

Mr. J. C. Lynn

S&E-COMP-RRF

Mr. Rodrigue

A&TS-PAT

Mr. L. D. Wofford, Jr.

A&TS-MS-IL (8)

A&TS-MS-IP (2)

A&TS-MS-H

A&TS-TU (6)

PM-PR-M

EXTERNAL

Scientific and Technical Information
Facility (25)

P. O. Box 33

College Park, Maryland 20740

Attn: NASA Representative (S-AK/RKT)

DISTRIBUTION (Concluded)

EXTERNAL (Concluded)

National Aeronautics & Space
Administration

Washington, D. C. 20546

Mr. Elmer Christiansen, MAL

Mr. Robert Bryson, MAL

Mr. Floyd Robertson, MAL

Mr. Warren Keller, SL

JPL California Institute of Technology
4800 Oak Grove Drive

Pasadena, California 91103

Mr. Paul Muller

Mr. Ray L. Newburn, Jr.

Stanford University

Department of Aeronautics &
Astronautics

Stanford, California 94305

Dr. Dan Debra

Dr. John V. Breakwell

Smithsonian Astrophysical
Observatory

60 Garden Street

Cambridge, Mass. 02139

Dr. Charles A. Lundquist

Dr. Colombo

Grumman Aircraft Engineering
Corporation

Bethpage, N. Y. 11714

Dr. Paul Savet

Hughes Research Laboratories

3011 Malibu Canyon Road

Malibu, Calif. 90265

Mr. Curtis Bell

Mr. Dale Sypma

Dr. Robert L. Forward

MIT, Charles Stark Draper Lab.

68 Albany Street

Cambridge, Mass. 02139

Mr. Milton B. Tragreser

General Oceanology, Inc.

27 Moulton Street

Cambridge, Mass. 02139

Dr. Lloyd G. D. Thompson

Air Force Cambridge Research
Laboratories

Lawrence G. Hanscom Field

Bedford, Mass. 01730

Mr. David Anthony

Dr. Zabo

Auburn University, Math Department

Auburn, Alabama 36830

Dr. Philip M. Fitzpatrick

Dr. John Cochran

NASA

Manned Spacecraft Center

Houston, Texas 77058

Mr. William Wollenhaupt

Dr. Philip Chapman

Mr. William Chapman

Mr. Don Incerto

NASA

Langley Research Center

Langley Field, Virginia

Hampton, Virginia 23365

Mr. A. G. Beswick